

MORE FEATURES. MORE RELIABLE. MORE AFFORDABLE.

DELV-2LCD7-CVGAD

- Aspect Ratio:** 16:9
Brightness: 400cd/m²
Contrast: 500:1
Resolution: 800x480
Viewing Angle: 140°/120° (H/V)
Size/Type: 7in LCD, LED backlight-Dual
Dimensions: 19.00x5.26x1.00 in
More info click here: [DELV-2LCD7-CVGAD](#)
Items Included:
12VDC Power Adapter, Power Supply Cable Clamp



Broadcast Composite VGA & DVI 7" 3RU Rackmount Monitor

The super slim Delvcam DELV-2LCD7-CVGAD monitor is perfect for TV news production, live events, post production, and broadcasting studios as well as TV broadcasting trucks, video surveillance, and other locations needing low cost, high-quality monitors.

This monitor pairs broadcast quality performance with multi-format flexibility and a wide range of supported resolutions! The dual 7", 16x9 screens in a thin rack mounted 3 RU design make this an exceptional confidence or production monitor.

Specifications

Special Functions: Image Flip, OSD Auto Color

Input: Per screen: Composite, VGA, AV, DVI
Output: Per screen: Composite, AV, VGA
Audio: N/A
Mount: Dual 7in rack mount with tilt capability
Weight: 5.64 lb

Battery Plate: N/A
Power : 14W
Input Current: 1A
Input Voltage: 7-24VDC

Formats/Rates

VGA: 640x400/56Hz, 720x400/70Hz/85Hz, 640x480/60Hz/66Hz/72Hz/85Hz, 800x600/60Hz/72Hz, 1024x768/60Hz/70Hz/75Hz, 1152x864/75 Hz, 1152x870/75Hz, 1280x960/60Hz, 1280x1024/75Hz/85Hz, 1600x1200/60Hz/65Hz/70Hz/85Hz, 1920x1080/60Hz

DVI: 640x400/56Hz, 720x400/70Hz/85Hz, 640x480/60Hz/66Hz/72Hz/85Hz, 800x600/60Hz/72Hz, 1024x768/60Hz/70Hz, 1152x864/75 Hz, 1152x870/75Hz, 1280x720/60Hz, 1280x1024/70Hz/85Hz, 1600x1200/65Hz/70Hz/85Hz, 1920x1080/60Hz