

# MORE FEATURES. MORE RELIABLE. MORE AFFORDABLE.

# **DELV-3GHD-17RD**

Aspect Ratio: 16:9

Brightness: 300cd/m<sup>2</sup>

Contrast: 700:1

Resolution: 1920x1080

Viewing Angle: 178°/178°(H/V)

Size/Type: 17.3in IPS

**Dimensions:** 19x1.73x19.98 in

More info

click here: DELV-3GHD-17RD

Items Included:

15VDC Power Supply, Tally Connector



# 1RU Rack Drawer 3G-SDI 17.3" Video Monitor with Cross Conversion

The Delvcam DELV-3GHD-17RD Rack Drawer Video Monitor offers space saving versatility with multiple image control functions. The 17.3-inch LCD monitor features HDMI-SDI cross conversion, an embedded audiometer, vector scope, wide viewing angles, and high-quality, full HD 1920x1080 resolution.

When not in use, the slim design allows the monitor to be folded down and slid into its metal 1RU rack drawer using a sturdy handle. Power automatically shuts off when in the drawer position with locking screws to secure it in place.

### **Specifications**

Special • Cross Functions: • Pictu

- Cross Conversion, Vectorscope
- Picture: Brightness, Contrast, Saturation, Tint, Sharpness, Color Temp, Red Gain, Green Gain
- Marker: Center, Aspect, Safety, Marker Color, Marker Mat, Thickness
- Function: Scan, Aspect, Underscan, H/V Delay, Check Field, Zoom, Freeze, DSLR
- Waveform: Peaking, Peaking Color, Peaking Level, False Color, Exposure, Exposure Level, Histogram
- · Audio: Volume, Level Meter, Audio Channel
- System: HDMI/SDI Convert, Color Bar, OSD Time, Backlight, Fan, Reset

Input: 3G-SDI, HDMI, DVI, Audio (L/R), Tally

Output: 3G-SDI, HDMI

Audio: Built-in Speakers, Earphone Jack, Audiometer

Mount: Rack Drawer

Weight: 18.96 lb

Operating Temperature:  $-20^{\circ}\text{C} \sim 60^{\circ}\text{C} (-4^{\circ}\text{F} \sim 140^{\circ}\text{F})$ Storage Temperature:  $-30^{\circ}\text{C} \sim 70^{\circ}\text{C} (-22^{\circ}\text{F} \sim 158^{\circ}\text{F})$ 

Battery Plate: N/A

A

Power: 32W Input Current: 2.8A

Input Voltage: 15VDC

#### Formats/Rates

3G-SDI: SMPTE-125M 480i(59.94) 1080i(60/59.94/50) 1080p (30/29.97/25/24/24sF/23.98/23.98sF) SMPTE-292M 1080p (30/29.97/25/24/24sF/23.98/23.98sF) SMPTE-296M 720p (60/59.94/50/30/29/25/24/23.98)

 $SMPTE-372M\ 720p(60/59.94/50)\ 1080i(29.97/25/24/23.98)\ 1080p\ (60/59.94/50/30/29.97/25/24/23.98)\ SMPTE-425M-AB\ -Level\ A\ \&\ Level\ B\ 1080p(60/59.94/50)\ 1080i(60/59.94/50)\ 720p\ (60/59.94/50/30/29.97/25/24/23.98)\ ITU-R\ BT.656\ 576i(50)$ 

HDMI: Full HD,HD 1080p, 1080i, 720p, 576p, 576i, 480p, 486i