

MORE FEATURES. MORE RELIABLE. MORE AFFORDABLE.

DELV-8LCD-SDI

Aspect Ratio: 4:3
Brightness: 250cd/m²
Contrast: 300:1
Resolution: 640x240, up to 1920x1080
Viewing Angle: 80°/70° (H/V)
Size/Type: 2in LCD, LED backlight
Dimensions: 19x14.13x1.73 in
**More info
click here:** [DELV-8LCD-SDI](#)



Items Included:

15VDC Power Adapter

1RU Rackmount 3G-SDI Video Monitor with Eight 2" LCDs

The DELV-8LCD-SDI 1RU rackmount video monitor panel with eight 2-inch, LED backlit LCD monitors features embedded audio meters, equalization, reclocking, and a UMD character function. Each monitor includes one 3G-SDI input and output as well as DIP switches that activate the audio meters and linear time codes which assist in audio/video production monitoring.

Functions are controlled through a RS422 computer interface.

Specifications

Special Functions: Equalization, Reclocking, Looping Outputs, Embedded Audio Meters, Linear Time Codes, UMD Character Function, RS422 Computer Interface

Input: One RS422 Computer Interface/Per Screen: one 3G-SDI

Output: Per Screen: one 3G-SDI

Audio: Embedded Audio Meters

Mount: 1RU Rack Mount

Weight: 3.43 lb

Battery Plate: N/A

Power : 23W

Input Current: 1.5A

Input Voltage: 12-24VDC

Formats/Rates

HDMI: Full HD-HD 1080p, 1080i, 720p, 576p, 576i, 480p, 468i

SDI: SMPTE-125M 480i(59.94), 1080i(60/59.94/50), 1080p(30/29.97/25/24/24sF/23.98/23.98sF (60/59.94/50/30/29.97/25/24/23.98

SDI: SMPTE-292M1080p (30/29.97/25/24/24sF/23.98/23.98sF), SMPTE-296M720p (60/59.94/50/30/29/25/24/23.98)

SDI: SMPTE-372M 720p(60/59.94/50), 1080i(29.97/25/24/23.98), 1080p, SMPTE-425M-AB 1080p(60/59.94/50)

Level A & Level B 720p(60/59.94/50/30/29.97/25/24/23.98), Level B2X1080i(60/59.94/50), ITU-R-BT 656:576i(50)